



SINGLE LEVER LOCKING SYSTEM

INFORMATION SHEET

OVERVIEW

The single lever locking system comes standard with every door. Our design is maintenance free, simple to use, and customizable. Rather than the two-latch system used by many companies, the Diamond Doors manual locking system uses a single lever to operate. This means that the lever unlocks both sides of the door simultaneously, which makes getting in and out of your building quick and easy. When the system is engaged, the locking fingers press against the locking catches pulling the door tight against the building. The system is designed to create an exceptional seal from the outside environment. This locking handle can be positioned on either side of door for quick and easy access. The locking systems are installed and set up in the factory. No onsite adjustment is required.

Every door is equipped with a safety single point lock switch for manual locking doors. For the door opener to operate, the safety switch must be completely engaged. This switch prevents operation of the bi-fold door while the door is locked, preventing structural damage to your door, locking system, and building. It also prevents the door opener from straining against a locked door and burning out.

WARRANTY

The door is free of manufacturing defects in material and workmanship for a period of two years. The door will not warp, crack, or buckle under normal intended use as a door.



FREQUENTLY ASKED QUESTIONS

Can I specify which side of the door the locking handle is on?

Yes, you can choose if you want the handle on the left or right side of the door. Customers often position the handle next to their pedestrian door.

Will the door still open if it is locked?

We equip our doors with a safety single point lock switch which prevents the door from opening when locked.