



FASTENERS

INFORMATION SHEET

OVERVIEW

Diamond Doors offers an optional fastener package to attach the bifold door insulation and cladding to the door frame.

These fasteners are a self-drilling #10-16 or #12-16 Tek Screw. Length depends on the door and added options, ranging from ¾ inch to one inch for uninsulated doors, or three inch or four inch for insulated doors. These Tek Screws are available in all Diamond Doors standard colours and are powder coated to prevent paint chipping during installation.

Tek Screws are fastened through the cladding, through the insulation (optional), and drilled into the frame of the door. We recommend using a drill instead of an impact driver to prevent unnecessary paint chipping.



TECHNICAL SPECS

Fastener Type: Self Drilling Tek Screw

Screw Size: #10-16, #12-16, 3/4", 1", 2", 3"

Finish: Powder Coating

Standard Colour: See Colour Chart

FREQUENTLY ASKED QUESTIONS

Can I provide my own fasteners?

Yes, you can. If you prefer to supply your own fasteners, Diamond Doors will provide you with the required amounts.

What style of fasteners does Diamond Doors recommend?

Diamond Doors recommends a self-drilling #10-16 or #12-16 Tek Screw.

Which colours are available for fasteners?

Fasteners are available in all standard Diamond Doors colours. You can view our colour chart using the QR code or button on this page.

